



ACRYLIC FLOOR SEAL

HAIL ACRYLIC FLOOR SEAL is a blend of acrylic polymers and latex resin designed to provide a tough, water-resistant, gloss seal.

HAIL ACRYLIC FLOOR SEAL is designed primarily as a base sealer for semi-porous floors prior to application of either **Hail Floor Polish** or **Hail High Solids Floor Polish**.

FEATURES

Hard wearing

Provides a tough, scuff resistant, gloss seal to withstand the heaviest traffic.

Versatile

Suitable on all semi-porous floors including thermoplastic, vinyl and rubber. It may also be used on concrete.

Easy to remove

Can be quickly and safely removed by applying **Hail Floor Polish Stripper**.

BENEFITS

Directions for use

Initial preparation - Sweep/vacuum the floor to remove dust and debris, remove old polish or wax using **Hail Floor Polish Stripper**. Ensure the floor is clean and dry before applying HAIL ACRYLIC FLOOR SEAL.

Application - Apply a thin even coat of HAIL ACRYLIC FLOOR SEAL using either a lamb's wool applicator or preferably an Abudawood Flat Mop. Allow this coat to dry completely before applying a second coat.

Depending on the floor traffic, this can be further coated with either **Hail Floor Polish** or **Hail High Solids Floor Polish**.

Floor Maintenance - The sealed floor should be regularly maintained using **Hail Spray Buff**. Either mopping or spray buffing techniques may be used.

Coverage - 5 litres of HAIL ACRYLIC FLOOR SEAL will cover approximately 370 sq. meters (4000 sq. ft.) with one coat depending on the porosity of the surface to be coated.

Pack Size

Available in 4 x 5 litre cartons.



Manufactured in Saudi Arabia By:
ABUDAWOOD INDUSTRIAL CO. (Ltd.)
Yanbu Al-Sinaiyah
Industrial License No. 398/SAD



Distributed By:
Abudawood Trading Co.
P.O. Box 6060, Jeddah 21442
Tel.: (02) 6293911 Fax: (02) 6293936