



## **ACRYLIC SEAL M 106**

*MIRIFIC ACRYLIC SEAL M 106* is a blend of acrylic polymers and latex resin designed to provide a tough, water-resistant, gloss seal.

*MIRIFIC ACRYLIC SEAL M 106* is designed primarily as a base sealer for semi-porous floors prior to application of SURESHINE M 105.

### **FEATURES**

### **BENEFITS**

#### ***Hard Wearing***

Provides a tough, scuff resistant, gloss seal to withstand the heaviest traffic.

#### ***Versatile***

Suitable on all semi-porous floors including thermoplastic, vinyl and rubber. It may also be used on concrete.

#### ***Easy to Remove***

Can be quickly and safely removed by applying...Stripper.

## **Directions for use**

---

**Initial Preparation** – Sweep/vacuum the floor to remove dust and debris, remove old polish or wax using...Stripper. Ensure the floor is clean and dry before applying MIRIFIC ACRYLIC SEAL M 106.

**Application** – Apply a thin even coat of MIRIFIC ACRYLIC SEAL M 106 using either a lambs wool applicator or preferably an Abudawood Flat Mop. Allow this coat to dry completely before applying a second coat.

Depending on the floor traffic, this can be further coated with **Mirific Sureshine M 105**.

**Floor Maintenance** – The Sealed floor should be regularly maintained using...Renovator or Spray N Buff. Either mopping or spray buffing methods may be used.

**Coverage** – 5 litres of MIRIFIC ACRYLIC SEAL M 106 will cover approximately 370 sq. meters (4000 sq. ft.) with one coat depending on the porosity of the surfaces to be coated.

## **Pack Size**

---

Available in 4 x 5 litre cartons.



Manufactured in Saudi Arabia By:  
**ABUDAWOOD INDUSTRIAL CO. (Ltd.)**  
Yanbu Al-Sinaiyah  
Industrial License No. 398/SAD



Distributed By:  
**Abudawood Trading Co.**  
P.O. Box 6060, Jeddah 21442  
Tel.: (02) 6293911 Fax: (02) 6293936