



FLOOR POLISH

ROCKY FLOOR POLISH is a blend of special acrylic polymers and waxes to provide a durable, detergent resistant, deep gloss surface.

FEATURES

Hard wearing

Provides a tough, scuff resistant, gloss finish which can withstand very heavy traffic.

Easy to maintain

The special acrylic polymers provide improved gloss and extended durability when the floor is regularly maintained using **Hail Spray Buff**.

Easy to remove

Metallised for quick and safe removal by applying **Rocky Floor Polish Stripper**.

Versatile

Protects and enhances many surfaces including vinyl, thermoplastic, linoleum, sealed wood, sealed cork, rubber and pitch-mastic floors.

BENEFITS

Directions for use

Initial preparation – Sweep/vacuum the floor to remove dust and debris, remove old polish or wax using **Rocky Floor Polish Stripper**. Ensure the floor is clean and dry before applying ROCKY FLOOR POLISH.

Application – Apply a thin even coat of ROCKY FLOOR POLISH using either a lambswool applicator or preferably an Abudawood Flat Mop. Allow this coat to dry completely before applying a second coat. For best results, apply three coats. The polish will dry to a high gloss finish in approximately one hour. The floor can then be opened to traffic.

Floor maintenance – The polished floor should be regularly maintained using **Hail Spray Buff**. Use either mopping or spray buffing methods.

Coverage – 1 gallon of ROCKY FLOOR POLISH will cover approximately 280 square meters (3000 square feet) with one coat depending on the porosity of the surface to be coated.

Pack Size

Available in 4 x 1 gallon cartons.



Manufactured in Saudi Arabia By:
ABUDAWOOD INDUSTRIAL CO. (Ltd.)
Yanbu Al-Sinaiyah
Industrial License No. 398/SAD



Distributed By:
Abudawood Trading Co.
P.O. Box 6060, Jeddah 21442
Tel.: (02) 6293911 Fax: (02) 6293936